

PRODUCT CATEGORY
CONTROL SYSTEM
& OPTIONAL PARTS



All indoor units are provided with wireless or wired remote controllers as standard equipment. Other options, such as individual and central remote controllers, are also available.

- C-002 Individual Control
- C-008 Control System List
- C-012 Optional Parts
- C-013 Optional Parts List
- C-018 Optional Parts Lineup

Wired remote controller (with touch panel)

UTY-RNRYZ5



Easy operation due to large high-resolution STN-LCD touch panel screen

- Touch screen LCD
- Built-in daily/weekly timer (ON/OFF, temperature, modes)
- Backlit screen for easy operation in the dark.
- Room temperature display
- Controls up to 16 indoor units
- Supports 12 languages: Chinese, Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, and Turkish
- nonpolar 2-core type

Up to 16 indoor units

Up to 1 group


High performance and compact size

A single remote controller controls each connected indoor unit and provides a weekly timer function and a variety of energy-saving options.



Accurate control for comfort

A thermo sensor built into the remote controller monitors room temperature accurately.



Energy saving controls

Custom Auto

- Maintains 2 separate setpoints for heating and cooling operations.
- Automatically switches between heating and cooling modes.

* Not available for some models

Auto-off timer



- While the Auto-timer is activated, if the set off time is specified as, for example, one hour, the power will automatically turn off one hour after the start of operation.
- A desired time frame can be specified for the Auto-off timer.
- The off-time can be set from 30 to 240 minutes.

2-setting weekly timer

Set temperature auto return

Setting temperature range limitation

Cooling set temp. 27°C, Heating set temp. 26°C




e.g.) Between 17:00 and 24:00 (over time hours), when the 1 hour set off time has elapsed, the system will automatically turn off the indoor unit as it

Features: Wired Remote Controller (Touch Panel)

Refrigerant cycle monitor (Option)

Wired Remote Controller (Touch Panel) will support to display some sensor values for maintenance and service support.


* This function is only supported by split units, using the H-Serial communication protocol! Example: ASYH30KMTB



Multi System Control*1


1) Lead Lag Operation

Standby Indoor Unit can be selected in lead lag operation. By this, the Indoor units will last longer than operating by nonstop.




2) Back up operation

In case of unexpected Indoor unit error, other Indoor units will start providing back up operation.



3) Lag Operation

In case of unexpected room temperature rise, other Indoor Units will start providing lag operation.



*1: "Lead Lag Setting" is an easy-to-use function for room temperature control when using multiple indoor units, while reducing the burden placed on each indoor unit.

If you wish to make use of this function, ensure you use indoor units equipped with a "Special Cooling" function. If you use indoor units that do not have a "Special Cooling" function, under certain conditions, there is a chance that "Backup operation" may not operate correctly, and the "Lead Lag Setting" function will not give the expected results. Additionally, for rooms that require strict conditions, such as server rooms, please consider other appropriate measures. Please note that we will not provide compensation for any damages suffered to your appliances or data as a result of using this function. For more details, please confirm with your nearest retail store.

Specifications

Model name	UTY-RNRYZ5
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 20.4
Weight (g)	220

DC 12 V is supplied by the indoor unit.

Wired Remote Controller

UTY-RLRY



- Various timer setup (ON / OFF / WEEKLY) are possible.
- The room temperature can be controlled by detecting the temperature accurately with Built-in thermo sensor.
- When a failure occurs, the error code is displayed.
- Error history. (Last 16 error codes can be accessed.)
- 2-wire type

Maximum Controllable
16 indoor units

Maximum Controllable
1 Group


High performance and compact size

In addition to the individual control, weekly timer, and various energy saving controls can be realized using only one remote controller.




High visibility and easy operation

- "Mode", "Set Temp", and "Fan" are displayed at large size on the top screen.
- Each function to be set is indicated by an icon.
- Control guide is displayed and operation is simple and straightforward.



Wired Remote Controller

UTY-RNNYM



- Simple operation with Built-in Weekly / Daily Timer.
- Control up to 16 indoor units.
- Up to 2 wired remote controllers can be connected to a single indoor unit.


Maximum Controllable
16 indoor units

Maximum Controllable
1 Group

Accurate and comfortable

Indoor temperature can be detected accurately by the inclusion of a thermo sensor in the body of the wired controller. This wired remote controller and the optional remote sensor allows flexibility in sensor location, suitable for all requirements.

Example of changing sensor



Built-in timers

Weekly timer: Possible to set ON/OFF time to operate twice each day of the week.
Setback timer: Possible to set temperature for two times spans and for each day of the week.
 At "Weekly timer" + "Set back timer" setup


Specifications

Model name	UTY-RLRY	UTY-RNNYM
Power Source	DC 12 V	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 17	120 × 120 × 18
Weight (g)	170	160

DC 12 V is supplied by the indoor unit.

Compact Wired Remote Controller

UTY-RCRYZ1



- Simple design to match the stylish interior
- Easy to install : Body of controller is designed to fit in European standard junction box
- Can be operated both by wireless and wired remote controller.
- 2-wire type


Maximum Controllable
1 single indoor unit

Maximum Controllable
1 Group

Large screen and simple display

- Although the size is compact, the screen is large
- Large letters makes it easy to see
- Operation is simple and easy-to-understand


- 1 Visible large letter
- 2 Touch key (Frequently-used operation is placed on the direct button)
- 3 Operation mode
- 4 Menu
- 5 Air flow
- 6 Built in IR reciever
- 7 LCD with backlight is clearly visible in the dark
- 8 Easy-to-understand pictograph display
- 9 LED is mounted for the ON/OFF key (Green light on when R.C. is turned on)



System overview


VRF connection

One indoor unit and one remote controller are connected in one non-polar and 2-wire remote controller system.



RAC (Room air conditioner) connection

One indoor unit and one remote controller are connected in one non-polar and 2-wire remote controller system.




Specifications

Model name	UTY-RCRYZ1
Power Source	DC12V
Dimensions (H × W × D) (mm)	86 × 86 × 44
Weight (g)	135

DC 12 V is supplied by the indoor unit.

Simple Remote Controller

UTY-RSRY / UTY-RHRY (Without operation mode)




Compact remote controller provides access to basic functions

- Up to 16 indoor units can be controlled with one remote controller.
- Suitable for hotels or offices as it is easily operated with no complex functions.
- Stylish design: Simple design to match the stylish interior.
- Large LCD screen & simple operation buttons
- Backlight: White colored backlight on monitor enable easy operation in dark.
- 2-wire type

Maximum Controllable
16 indoor units
Maximum Controllable
1 Group

Corresponding to various applications

- **Vertical louver control:** Vertical air flow direction can be adjusted for Duct types with auto louver and Cassette types, which are installed in hotels and conference rooms, can be adjusted.
- **Room temperature set point limitation:** The Simple Remote Controller can manage to energy saving operation in small buildings without the central control unit.
- **Built in room temperature sensor:** The Simple Remote Controller detects actual room temperature and controls room climate accuracy.



Simple Remote Controller

UTY-RSRYM



UTY-RSRYM

Compact remote controller provides access to basic functions

- Up to 16 indoor units can be controlled with one remote controller.
- Suitable for hotels or offices as it is easily operated with no complex functions.
- Backlight enables easy operation in a darkened room.
- 3-wire type

Maximum Controllable
16 indoor units
Maximum Controllable
1 Group

Easy-to-use operation

- Provides access to basic operations, such as Start / Stop, Fan control, Operation mode switching, and Room temperature setting.
- A large On / Off button is provided in the centre of the remote controller for easy operation.
- Can be used jointly with other individual control unit.
- Following an error display, diagnostics can be carried out on the controller.

Specifications

Model name	UTY-RSRY	UTY-RHRY	UTY-RSRYM
Power Source	DC 12 V	DC 12 V	DC 12 V
Dimensions (H × W × D) (mm)	120 × 75 × 19.4	120 × 75 × 19.4	120 × 75 × 19.4
Weight (g)	120	120	120

DC 12 V is supplied by the indoor unit.

Wired Remote Controller

UTY-RVNYM




Maximum Controllable
16 indoor units
Maximum Controllable
1 Group

Hi-grade individual control using various functions.

- 3.7-inch LCD backlight screen.
- Supporting various Energy Saving functions with simple operation.
- Multiple Language Support.
(English, German, French, Spanish, Russian, Portuguese, Italian, Greek, and Turkish)

High visibility and Easy operation

- Icon display of effectual functions.
- Main functions in large icons: "Mode", "Set Temp", and "Fan".
- Easy to operate by Control guide display.
- Simple operation with easy 4-way navigation pad.



High performance and compact size


- In addition to the individual control, various energy saving controls can be realized using only one remote controller.



Various energy saving control


Weekly Timer function

- Can be set up to 8 times per day (On/Off, mode, Temp)
- 2 pattern settings (i.e. Summer/Winter setting) are available.



Auto OFF Timer

- Set Temperature Auto Return
- Set Temperature Upper and Lower Limit Setting



Specifications















Model name	UTY-RVNYM
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 21.3
Weight (g)	220

DC 12 V is supplied by the indoor unit.

Split Control System List-INVERTER

Country		🇸🇬 for Singapore		🇻🇳 for Vietnam		Common models								
Type	Wall Mounted	Circular Flow Cassette	Wall Mounted		Compact Cassette		Circular Flow Cassette	Ceiling	Slim Duct	Medium Static Pressure Duct	High Static Pressure Duct		Big Duct	
Model No.	ASAG 09/12/18/24/30 CMTA	AUAH24/36CRLA	ASAG 09/12/18/24 CPTA-V	ASAG09LLTB-V ASAG12LLTA-V	AUXG18/24KVLA	AUYG18LVLB AUYG24LVLA	AUXG 18/24/30/36/45/54 KRLB	ABYG 18/24/30/36/45 KRTA	ARXG18KLLAP	ARXG24/30/36/45KMLA	ARXG45/54KHTB	ARYG60LHTA	ARYG72/90LHTA	
Controllers														
Wired Remote Controller		UTY-RNRYZ5	UTY-RNRYZ5			UTY-RNRYZ5		UTY-RNRYZ5	UTY-RNRYZ5	UTY-RNRYZ5	UTY-RNRYZ5	UTY-RNRYZ5	UTY-RNRYZ5	
		UTY-RLRY	UTY-RLRY			UTY-RLRY		UTY-RLRY	UTY-RLRY	UTY-RLRY	UTY-RLRY	UTY-RLRY	UTY-RLRY	
						UTY-RVNYM	UTY-RVNYM	UTY-RVNYM	UTY-RVNYM	UTY-RVNYM		UTY-RVNYM	UTY-RVNYM	
						UTY-RNNYM	UTY-RNNYM	UTY-RNNYM	UTY-RNNYM	UTY-RNNYM		UTY-RNNYM	UTY-RNNYM	
Compact Wired Remote Controller		UTY-RCRYZ1	UTY-RCRYZ1			UTY-RCRYZ1		UTY-RCRYZ1	UTY-RCRYZ1	UTY-RCRYZ1	UTY-RCRYZ1	UTY-RCRYZ1	UTY-RCRYZ1	
Simple Remote Controller	 2-wire type 3-wire type	UTY-RSRY UTY-RHRY	UTY-RSRY UTY-RHRY			UTY-RSRY UTY-RHRY UTY-RSNYM	UTY-RSNYM	UTY-RSRY UTY-RHRY UTY-RSNYM	UTY-RSRY UTY-RHRY	UTY-RSRY UTY-RHRY UTY-RSNYM	UTY-RSRY UTY-RHRY	UTY-RSNYM	UTY-RSRY UTY-RHRY UTY-RSNYM	
Wireless remote controller						UTY-LNTY								
IR Receiver Kit	 For Cassette		UTY-LBTYC					UTY-LBTYC						
	 For Duct								UTY-LBTYM	UTY-LBTYM	UTY-LBTYM	UTY-LRHYM	UTY-LBTYM UTY-LRHYM	
	 For Ceiling							UTY-LBTYH						
Interface	MODBUS™ Convertor		UTY-VMSX	UTY-VMSX			UTY-VMSX	UTY-VMSX	UTY-VMSX	UTY-VMSX	UTY-VMSX	UTY-VMSX	UTY-VMSX	
	KNX® Convertor		UTY-VKSX	UTY-VKSX			UTY-VKSX	UTY-VKSX	UTY-VKSX	UTY-VKSX	UTY-VKSX	UTY-VKSX	UTY-VKSX	
	Wireless LAN Adapter (USB type)		UTY-TFSXF3											
	Wireless LAN Adapter			UTY-TFSXZ2			UTY-TFSXZ2	UTY-TFNXZ3	UTY-TFSXZ2	UTY-TFSXZ2	UTY-TFSXZ2	UTY-TFSXZ2	UTY-TFNXZ3	UTY-TFSXZ2
	External switch controller		UTY-TERX	UTY-TERX			UTY-TERX	UTY-TERX	UTY-TERX	UTY-TERX	UTY-TERX	UTY-TERX	UTY-TERX	UTY-TERX
	Network Converter for Single Split	 DC Power Supply Type AC Power Supply Type	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV			UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV	UTY-VTGX UTY-VTGXV

Multi-Split Control System List-INVERTER

		for Singapore												Indoor Units for 2-unit, 3-unit, 4-unit, 5-unit Multi-split											
Type		Wall Mounted			Cassette	Duct			Wall Mounted				Cassette	Duct											
Series		Designer Series		Standard Series	Compact 4-way Flow Grid type Series	Mini	Medium Static Pressure		Designer Series		Standard Series		Compact 4-way Flow Grid type Series	Mini (With drain pump)	Slm (With drain pump)	Medium Static Pressure									
Model No.		ASAH09/12CMCA	ASAH09/12CETA ASAH09/12CETA-B	ASAH18/24CMTA	AUAH12/14/18CVLA	ARAH 09/12/14/18 CSLAP	ARAH24CMTAP		ASYG07/09/12/14KGTE	ASYG07/09/12/14KETE ASYG07/09/12/14KETE-B	ASYG07/09/12/14KMCE	ASYG18/22/24KMTE	AUXG 07/09/12/14/18/22 KVLA	ARXG 07/09/12/14/18 KSLAP	ARXG 07/09/12/14/18 KLLAP	ARXG22KMLB									
Controllers	Wired Remote Controller		• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5	• UTY-RNRYZ5	• UTY-RNRYZ5	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5+ UTY-TWRXZ2	• UTY-RNRYZ5	• UTY-RNRYZ5	• UTY-RNRYZ5	• UTY-RNRYZ5									
			• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY	• UTY-RLRY	• UTY-RLRY	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY+ UTY-TWRXZ2	• UTY-RLRY	• UTY-RLRY	• UTY-RLRY	• UTY-RLRY								
														• UTY-RVNYM	• UTY-RVNYM	• UTY-RVNYM	• UTY-RVNYM								
														• UTY-RNNYM	• UTY-RNNYM	• UTY-RNNYM	• UTY-RNNYM								
	Compact Wired Remote Controller		• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1	• UTY-RCRYZ1	• UTY-RCRYZ1	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1+ UTY-TWRXZ2	• UTY-RCRYZ1	• UTY-RCRYZ1	• UTY-RCRYZ1	• UTY-RCRYZ1								
	Simple Remote Controller	 2-wire type	• UTY-RSRY+ UTY-TWRXZ2	• UTY-RSRY+ UTY-TWRXZ2	• UTY-RSRY+ UTY-TWRXZ2	• UTY-RSRY	• UTY-RSRY	• UTY-RSRY	• UTY-RSRY UTY-RHRY+ UTY-TWRXZ2	• UTY-RSRY UTY-RHRY+ UTY-TWRXZ2	• UTY-RSRY UTY-RHRY+ UTY-TWRXZ2	• UTY-RSRY UTY-RHRY+ UTY-TWRXZ2	• UTY-RSRY UTY-RHRY+ UTY-TWRXZ2	• UTY-RSRY UTY-RHRY UTY-RSNYM	• UTY-RSRY UTY-RHRY UTY-RSNYM	• UTY-RSRY UTY-RHRY UTY-RSNYM	• UTY-RSRY UTY-RHRY UTY-RSNYM								
	Wireless Remote Controller		• UTY-LNTY	• UTY-LNTY	• UTY-LNTY	• UTY-LNTY								• UTY-LNTY											
IR Receiver Kit	 For Duct					• UTY-LBVYM	• UTY-LBVYM							• UTY-LBTYM	• UTY-LBTYM	• UTY-LBTYM									
Interface	MODBUS™ Convertor		• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX	• UTY-VMSX									
	KNX® Convertor		• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX	• UTY-VKSX									
	Wireless LAN Adapter (USB type)		• UTY-TFSXF3	• UTY-TFSXF3	• UTY-TFSXF3				• UTY-TFSXF3	• UTY-TFSXF3	• UTY-TFSXF3	• UTY-TFSXF3	• UTY-TFSXF3												
	Wireless LAN Adapter					• UTY-TFNXZ3	• UTY-TFNXZ3	• UTY-TFNXZ3						• UTY-TFSXZ2	• UTY-TFSXZ2	• UTY-TFSXZ2	• UTY-TFSXZ2								
	External switch controller		• UTY-TERX	• UTY-TERX	• UTY-TERX	• UTY-TERX	• UTY-TERX	• UTY-TERX	• UTY-TERX+ UTY-TWRXZ2	• UTY-TERX+ UTY-TWRXZ2	• UTY-TERX+ UTY-TWRXZ2	• UTY-TERX+ UTY-TWRXZ2	• UTY-TERX+ UTY-TWRXZ2	• UTY-TERX	• UTY-TERX	• UTY-TERX	• UTY-TERX								
	Network Convertor for Single Split	 DC Power Supply Type AC Power Supply Type	• UTY-VTGX+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2	• UTY-VTGX	• UTY-VTGX	• UTY-VTGX	• UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2	• UTY-VTGX+ UTY-TWRXZ2 or UTY-VTGXV+ UTY-TWRXZ2	• UTY-VTGX UTY-VTGXV	• UTY-VTGX UTY-VTGXV	• UTY-VTGX UTY-VTGXV	• UTY-VTGX UTY-VTGXV								

Auto Louver Grille Kit

UTD-GXTA-W / UTD-GXTB-W




Simple flat Auto Louver will provide comfort airflow and harmonize with luxury interior.




Flexible Control

- **Operation with indoor unit**
Auto Louver can be operated by synchronizing remote controller of indoor unit.
- **UP and Down auto swing**
 - Auto airflow direction and auto swing
 - 4 steps selectable
- **Auto-closing louver**
When operation of indoor unit is stopped, the louver will automatically close.



Dimensions



Model Name	W1	W2	H1	H2	D1	D2
UTD-GXTA-W	683	645	180	148	9	84
UTD-GXTB-W	883	845				

Unit:mm

Specifications

Model name	UTD-GXTA-W		UTD-GXTB-W	
Applicable Indoor Unit	ARAH09/12/14CSLAP ARXG07/09/12/14KSLAP ARXG07/09/12/14KLLAP		ARXG18KLLAP ARAH18CSLAP ARXG18KSLAP	
Power Supply	Connecting with Control box of indoor unit			
Fixing of Auto Louver Grille	Screw fixing to Flange or Square Duct			
Extension Square Duct Limit	1.0m (Max. duct length between indoor unit and Grille)			
Net Dimension (H × W × D)	mm	180 × 683 × (84 + 9)		180 × 883 × (84 + 9)
Weight	Net	2.0 (4.4)		2.5 (5.6)
	Gross	3.0 (6.7)		3.5 (7.8)
Color	White			
Louver Motor	Stepping Motor			
Accessories	Fitting Flame, etc.			
Operation range	Cooling	°C	18 to 32	
		% RH	80% or less	
	Heating	°C	16 to 30	

Optional Parts List For Split & Multi-Split




Split Optional Parts List-INVERTER

Country		🇸🇬 for Singapore		🇻🇳 for Vietnam		Common models								
Type		Wall Mounted	Circular Flow Cassette	Wall Mounted		Compact Cassette		Circular Flow Cassette	Ceiling	Slim Duct	Medium Static Pressure Duct	High Static Pressure Duct	Big Duct	
Model No.		ASAG 09/12/18/24/30 CMTA	AUAH24/36CRLA	ASAG 09/12/18/24 CPTA-V	ASAG09LLTB-V ASAG12LLTA-V	AUXG18/24KVL A	AUYG18LVLB AUYG24LVLA	AUXG 18/24/30/36/45/54 KRLB	ABYG 18/24/30/36/45 KRTA	ARXG18KLLAP	ARXG24/30/36/45KMLA	ARXG45/54KHTB	ARYG60LHTA	ARYG72/90LHTA
Others			● UTY-SHZXC					● UTY-SHZXC						
										● UTY-XSZXZ1	● UTY-XSZXZ1	● UTY-XSZXZ1	● UTY-XSZXZ1	● UTY-XSZXZ1
			● UTG-UKYA-W UTG-UKYA-B			● UTG-UFYF-W	● UTG-UFYD-W	● UTG-UKYA-B UTG-UKYA-W UTG-UKYC-W						
										● UTD-GXTB-W				
											● UTD-RF204 UTD-SF045T			
									● UTR-DPB24T		● UTZ-PX1NBA			● UTZ-PX1NAB
			● UTG-AKXA-W					● UTG-AKXA-W						
			● UTG-BKXA-W					● UTG-BKXA-W						
			● UTZ-VXRA			● UTZ-VXAA	● UTZ-VXAA	● UTZ-VXRA						
			● UTR-YDZK			● UTR-YDZB	● UTR-YDZB	● UTR-YDZK						
			● UTZ-KXRA			● UTZ-KXGC	● UTZ-KXGC	● UTZ-KXRA						
			● Accessory		● UTR-FA16-7									
											● UTD-LF25NA	● UTD-LF60KA		● UTD-LFKA
					● UTZ-RXLA									
									● UTP-FX24A (18/24) UTP-FX35A (30/36/45)					
External Connect Kit / Communication Kit			● UTY-TWRXZ2						● UTY-TWRXZ3					
			● UTY-XCSXZ2	● UTY-XCSX		● UTY-XCSX		● UTY-XCSX	● UTY-XCSX			● UTY-XCSX		● UTY-XCSX
				● UTZ-GXRA		● UTZ-GXRA		● UTZ-GXRA	● UTZ-GXEA			● UTZ-GXEA		
			● UTY-XWZXZ5	● UTY-XWZXZG		● UTY-XWZXZG	● UTY-XWZX	● UTY-XWZXZG	● UTY-XWZXZG	● UTY-XWZXZG	● UTY-XWZXZG	● UTY-XWZXZG	● UTY-XWZXZG	● UTY-XWZXZG
								● UTY-XWZXZ3 (30/36/45/54)	● UTY-XWZXZ3 (30/36/45)		● UTY-XWZXZ3 (30/36/45)	● UTY-XWZXZ3	● UTY-XWZXZ2	● UTY-XWZXZ3
												● UTD-EC55A		

Multi-Split Optional Parts List-INVERTER

		for Singapore												Indoor Units for 2-unit, 3-unit, 4-unit, 5-unit Multi-split											
Type		Wall Mounted				Cassette	Duct			Wall Mounted				Cassette	Duct										
Series		Designer Series		Standard Series	Compact 4-way Flow Grid type Series	Mini	Medium Static Pressure			Designer Series		Standard Series		Compact 4-way Flow Grid type Series	Mini (With drain pump)	Slim (With drain pump)	Medium Static Pressure								
Model No.		ASAH09/12CMCA	ASAH09/12CETA ASAH09/12CETA-B	ASAH18/24CMTA	AUAH12/14/18CVLA	ARAH 09/12/14/18 CSLAP	ARAH24CMTAP			ASYG07/09/12/14KGTE	ASYG07/09/12/14KETE ASYG07/09/12/14KETE-B	ASYG07/09/12/14KMCE	ASYG18/22/24KMTE	AUXG 07/09/12/14/18/22 KVLVA	ARXG 07/09/12/14/18 KSLAP	ARXG 07/09/12/14/18 KLLAP	ARXG22KMLB								
Others	Remote Sensor Unit					• UTY-XSZXZ1	• UTY-XSZXZ1								• UTY-XSZXZ1	• UTY-XSZXZ1	• UTY-XSZXZ1								
	Cassette Grille				• UTG-UFYF-W									• UTG-UFYF-W											
	Auto Louver Grille Kit					• UTD-GXTA-W (09/12/14) UTD-GXTB-W (18)									• UTD-GXTA-W (07/09/12/14) UTD-GXTB-W (18)	• UTD-GXTA-W (07/09/12/14) UTD-GXTB-W (18)									
	Flange																• UTD-RF204 UTD-SF04ST								
	Drain Pump Unit																• UTZ-PX1NBA								
	Fresh Air Intake Kit <small>For Compact Cassette</small>				• UTZ-VXAA										• UTZ-VXAA										
	Air Outlet Shutter Plate <small>For Compact Cassette</small>				• UTR-YDZB										• UTR-YDZB										
	Insulation Kit For High Humidity <small>For Compact Cassette</small>				• UTZ-KXGC										• UTZ-KXGC										
	Silver ion filter	• UTR-FA16-5	• UTR-FA16-5	• UTR-FA16-5	• UTD-HFAA	• UTD-HFTA (09/12/14) UTD-HFTB (18)	• UTD-HFNB																		
	Silver ion filter II (PM2.5+Anti virus)								• UTR-FA16-7	• UTR-FA16-7	• UTR-FA16-7	• UTR-FA16-7													
Long-life filter						• UTD-LFDB											• UTD-LF25NA								
External Connect Kit / Communication Kit	Communication Kit	• UTY-TWRXZ2	• UTY-TWRXZ2	• UTY-TWRXZ2					• UTY-TWRXZ2	• UTY-TWRXZ2	• UTY-TWRXZ2	• UTY-TWRXZ2													
	External input and output PCB	• UTY-XCSXZ2	• UTY-XCSXZ2	• UTY-XCSXZ2	• UTY-XCSX	• UTY-XCSX	• UTY-XCSX		• UTY-XCSXZ2	• UTY-XCSXZ2	• UTY-XCSXZ2	• UTY-XCSXZ2	• UTY-XCSX												
	External input and output PCB box				• UTZ-GXEA	• UTZ-GXEA	• UTZ-GXEA																		
	External Connect Kit (For Indoor)	• UTY-XWZXZ5	• UTY-XWZXZ5	• UTY-XWZXZ5	• UTY-XWZXZG	• UTY-XWZXZG	• UTY-XWZXZG		• UTY-XWZX UTY-XWZXZ5	• UTY-XWZX UTY-XWZXZ5	• UTY-XWZX UTY-XWZXZ5	• UTY-XWZX UTY-XWZXZ5	• UTY-XWZXZG	• UTY-XWZXZG	• UTY-XWZXZG	• UTY-XWZXZG	• UTY-XWZXZG								

Optional Parts Lineup For Split & Multi-Split



Split / Multi-Split Optional Parts Lineup

Controllers

For Individual & Centralized Control

Wired Remote Controller
UTY-RNRYZ5



Wired Remote Controller
UTY-RLRY



Wired Remote Controller
UTY-RVNYM



Compact Wired Remote Controller
UTY-RCRYZ1



Wired Remote Controller
UTY-RNNYM



Simple Remote Controller
UTY-RSRY with operation mode UTY-RHRY without operation mode



Simple Remote Controller
UTY-RSNYM



Wireless Remote Controller
UTY-LNTY



Others

For Duct type

Remote Sensor Unit
UTY-XSZXZ1

New amenity space can be offered by installing the Remote sensor.



IR Receiver Kit
UTY-LRHYM



UTY-LBTYM



UTY-LBVMY **NEW**



Long-Life Filter

UTD-LF60KA UTD-LF25NA
UTD-LFDB



Flange

UTD-RF204 (Round)



UTD-SF045T (Square)



Drain Pump Unit

UTZ-PX1NBA / UTZ-PX1NAB



Silver ion filter **NEW**

UTD-HFTA / UTD-HFTB / UTD-HFNB



Auto Louver Grille Kit

UTD-GXTA-W (For 07-14 type)



For Wall Mounted type

Remote controller holder
UTZ-RXLA



Silver ion filter **NEW**
UTR-FA16-5




Silver ion filter II (PM2.5+Anti virus)
UTR-FA16-7



For Ceiling type

Drain Pump Unit
UTR-DPB24T



IR Receiver unit
UTY-LBTYH



L type piping kit
UTP-FX24A (For 18-24 type)
UTP-FX35A (For 30-45 type)



Split / Multi-Split Optional Parts Lineup

Others

For Cassette type		
Remote Sensor Unit UTY-XSZXZ1 New amenity space can be offered by installing the Remote sensor.	Human sensor kit UTY-SHZXC For Circular Flow Cassette	IR Receiver Kit UTY-LBTYC For Circular Flow Cassette
Cassette Grille UTG-UFYD-W For Compact Cassette	Cassette Grille UTG-UFYF-W For Compact Cassette	Cassette Grille UTG-UKYC-W For Circular Flow Cassette
Cassette Grille (Black panel) UTG-UKYA-B For Circular Flow Cassette	Cassette Grille (with Remote Controller) UTG-UKYA-W For Circular Flow Cassette	Wide Panel UTG-AKXA-W
Panel Spacer UTG-BKXA-W 	Fresh Air Intake Kit UTZ-VXAA	Fresh Air Intake Kit UTZ-VXRA
Insulation Kit For High Humidity UTZ-KXRA / UTZ-KXGC	Air Outlet Shutter Plate UTR-YDZB For Compact Cassette Shuts the air outlet when only using as 3 blow out.	Air Outlet Shutter Plate UTR-YDZK Shuts the air outlet when only using as 3 blow out.
Silver ion filter NEW UTD-HFAA For Compact Cassette		
Service & Maintenance		
Service Monitoring Tool UTY-ASSX		

Communication devices

Communication Kit / External input and output PCB / Box		
Communication Kit UTY-TWRXZ2 / UTY-TWRXZ3	External input and output PCB UTY-XCSXZ2 / UTY-XCSX	External input and output PCB Box UTZ-GXRA / UTZ-GXEA

Communication system

External Connect Kit / External Control set		
External Connect Kit For Indoor Unit UTY-XWZX / UTY-XWZXZG UTY-XWZXZ5	External Control Set For Indoor Unit UTD-ECS5A	External Connect Kit For Outdoor Unit UTY-XWZXZ3 / UTY-XWZXZ2

Convertors / Adaptors

External device		
Wireless LAN Adapter UTY-TFNXZ3 UTY-TFSXZ2 UTY-TFSXF3	Modbus Converter UTY-VMSX	KNX Converter UTY-VKSX
External Switch controller UTY-TERX	Network converter UTY-VTGX UTY-VTGXV DC Power Supply Type AC Power Supply Type	

Function list

Type	Model name	For Indoor unit			For Outdoor unit		
		UTY-XWZX	UTY-XWZXZ5	UTD-ECS5A	UTY-XWZXZ2	UTY-XWZXZ3	UTY-XWZXZ4
Input	Control	●	●	●	-	-	-
	Peak cut	-	-	-	●	●	-
	Low noise	-	-	-	●	●	-
	Priority	-	-	-	-	●	-
Output	Emergency stop	-	-	-	-	●	-
	Operation status	●	●	●	●	●	-
	Error status	-	●	●*1	●	●	-
	Fresh air control	-	-	●*2	-	-	-
	Auxiliary heater	-	-	●*3	-	-	-
	Preparation	-	-	●*4	-	-	-
	Base heater	-	-	-	-	-	●

* 1 : This function has been had only wall mounted model such as LT, LU, and LM.
 * 2 : This function has been had only ducted model, cassette model, and ceiling mode.

* 3 : This function has been had only ducted model.
 * 4 : This cable is necessary for some ducted model.